

Titanium Pipe Schedule
ANSI/ASME B36.19 (for S Sizes) B36.10 (for non-S sizes)

Wall Thickness (inches)
Weight per foot (pounds)

NPS Desig.	O.D. (in)	Nominal Wall Thickness							
		5	5S	10	10S	40	40S	80	80S
1/8	0.405	0.035	x	0.049	0.049	0.068	0.068	0.095	0.095
		0.080	x	0.107	0.107	0.141	0.141	0.181	0.181
1/4	0.540	0.049	x	0.065	0.065	0.088	0.088	0.119	0.119
		0.148	x	0.190	0.190	0.244	0.244	0.308	0.308
3/8	0.675	0.049	x	0.065	0.065	0.091	0.091	0.126	0.126
		0.188	x	0.244	0.244	0.327	0.327	0.425	0.425
1/2	0.840	0.065	0.065	0.083	0.083	0.109	0.109	0.147	0.147
		0.310	0.310	0.386	0.386	0.490	0.490	0.626	0.626
3/4	1.050	0.065	0.065	0.083	0.083	0.113	0.113	0.154	0.154
		0.393	0.393	0.493	0.493	0.651	0.651	0.848	0.848
1	1.315	0.065	0.065	0.109	0.109	0.133	0.133	0.179	0.179
		0.499	0.499	0.808	0.808	0.966	0.966	1.250	1.250
1-1/4	1.660	0.065	0.065	0.109	0.109	0.140	0.140	0.191	0.191
		0.637	0.637	1.039	1.039	1.308	1.308	1.724	1.724
1-1/2	1.900	0.065	0.065	0.109	0.109	0.145	0.145	0.200	0.200
		0.733	0.733	1.200	1.200	1.564	1.564	2.089	2.089
2	2.375	0.065	0.065	0.109	0.109	0.154	0.154	0.218	0.218
		0.923	0.923	1.518	1.518	2.102	2.102	2.890	2.890
2-1/2	2.875	0.083	0.083	0.120	0.120	0.203	0.203	0.276	0.276
		1.424	1.424	2.032	2.032	3.333	3.333	4.408	4.408
3	3.500	0.083	0.083	0.120	0.120	0.216	0.216	0.300	0.300
		1.743	1.743	2.492	2.492	4.359	4.359	5.899	5.899
3-1/2	4.000	0.083	0.083	0.120	0.120	0.226	0.226	0.318	0.318
		1.998	1.998	2.861	2.861	5.241	5.241	7.195	7.195
4	4.500	0.083	0.083	0.120	0.120	0.237	0.237	0.337	0.337
		2.253	2.253	3.230	3.230	6.208	6.208	8.621	8.621
5	5.563	0.109	0.109	0.134	0.134	0.258	0.258	0.375	0.375
		3.653	3.653	4.470	4.470	8.411	8.411	11.955	11.955
6	6.625	0.109	0.109	0.134	0.134	0.280	0.280	0.432	0.432
		4.364	4.364	5.345	5.345	10.917	10.917	16.440	16.440